

Datenblatt Art. 720.047

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

CHIP-LED-Strahler 120W

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 230V~	Rated current / rated voltage	16A / 230V~
Frequenz	50z	Frequency	50z
Netzanschluss		Power supply	
Zuleitung Gummischlauchleitung	2,0m H07RN-F 3G1,5mm²	Supply cable Rubber cable	2,0m H07RN-F 3G1,5mm²
Stecker Steckertyp	CEE 7/7 (Type E/F) Zentralstecker	Plug Plug type	CEE 7/7 (Type E/F) Central plug
Funktionsmodule		Function modules	
120W SAMSUNG-LED-CHIP		120W SAMSUNG-LED-CHIP	
Abstrahlwinkel LED	120°	Radiation angle LED	120°
Lichtstrom	10200Lm	Luminous flux	10200Lm
Farbtemperatur	4000K	Colour temperature	4000K
Einsatzbereich	-15 bis +45°C	Application area	-15 to +45°C
Weitere Produkteigenschaften		Further product attributes	
Abmessungen	410x310x60mm	Dimensions	410x310x60mm
Gewicht	5,6kg	Weight	5,6kg
Material Gehäuse: Aluminium-Druckguss		Material Housing: Aluminium die-cast	
Sicherheitsglas austauschbar Brenndauer	>50.000 h	Safety glass interchangeable Burning time	>50.000 h
Lieferumfang 1x CHIP-LED-Strahler 120W		Scope of delivery 1x CHIP-LED-spotlight 120W	
Im Karton verpackt		in carton packed	

Umgebungsbedingungen		Environmental conditions	
Schutzart	IP65	Protection type	IP65
Konformität / Approbation		Conformity / Approval	
Bauart geprüft	CE	Type approved	CE
Energieeffizienzklasse	A+	Energy class	A+

Zeichnung
BAN0034000

Drawing



